

Safety data sheet
according to UK REACH

Page 1/14

Printing date 08.07.2025

Revision: 08.07.2025

Version number 16.08 (replaces version 16.07)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** Formaldehyde 37-38% w/w stabilized with methanol

· **Article number:** 1328

· **CAS Number:**

50-00-0

· **EC number:**

200-001-8

· **Index number:**

605-001-00-5

· **Application of the substance / the mixture** Laboratory chemicals

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

PANREAC QUIMICA S.L.U.

C/Garraf 2

Polígono Pla de la Bruguera

E-08211 Castellar del Vallès (Barcelona)

Tel. (+34) 937 489 400

Fax. (+34) 937 489 401

e-mail: product.safety@itwreagents.com

· **Further information obtainable from:** email: product.safety@panreac.com

· **1.4 Emergency telephone number:**

Single telephone number for emergency calls: 112 (EU)

Tel.: (+34) 937 489 499

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1B H350 May cause cancer.

STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.

(Contd. on page 2)

GB

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 1)

STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The substance is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS05 GHS06 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
formaldehyde
methanol
- **Hazard statements**
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H350 May cause cancer.
H370 Causes damage to the central nervous system and the visual organs.
H335 May cause respiratory irritation.
- **Precautionary statements**
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see on this label).
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.1 Substances**
- **CAS No. Description**
50-00-0 formaldehyde
- **Identification number(s)**
- **EC number:** 200-001-8
- **Index number:** 605-001-00-5

(Contd. on page 3)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 2)

· Dangerous components:

CAS: 67-56-1 EINECS: 200-659-6 Reg.nr.: 01-2119433307-44-XXXX	methanol Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	>10-≤15%
---	--	----------

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider.

Immediately remove any clothing soiled by the product.

Remove breathing equipment only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Involve doctor immediately.

· After inhalation:

Take affected persons into fresh air and keep quiet.

If breathing stops: mouth-to-mouth respiration or mechanical ventilation, oxygen mask if necessary.

Immediately call a physician.

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

· After skin contact:

Wash off with plenty of water.

Call a doctor immediately.

Immediately wash with water and soap and rinse thoroughly.

Immediately remove any clothing soiled by the product.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

make victim drink water (maximum of 2 drinking glasses)

A person vomiting while laying on their back should be turned onto their side.

Do not induce vomiting; call for medical help immediately.

Make victim drink ethanol (e.g. 1 drink glass off a 40 % alcoholic beverage).

· 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulty

Dizziness

Headache

Cramp

Disorientation

Dizziness

Coughing

Allergic reactions

· 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Mentioning methanol ingestion.

GB

(Contd. on page 4)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide
Combustible.
Formaldehyde
- **5.3 Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Contain escaping vapours with water.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
Wear protective equipment. Keep unprotected persons away.
Avoid substance contact.
Do not inhale steams/aerosols.
- **6.2 Environmental precautions:**
Prevent from spreading (e.g. by damming-in or oil barriers).
Keep contaminated washing water and dispose of appropriately.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Clean up affected area.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Work only in fume cupboard.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Keep receptacles tightly sealed.

(Contd. on page 5)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 4)

- **Information about storage in one common storage facility:**
Do not store with the following type of product
strong oxidants
gases
- **Further information about storage conditions:**
Storage in a well-ventilated place.
Keep container tightly sealed.
Open receptacle only under localised extractor facilities.
Store receptacle in a well ventilated area.
Store under lock and key and with access restricted to technical experts or their assistants only.
Accessible for authorised persons only.
- **Recommended storage temperature:** Room Temperature
- **Storage class:** 6.1 C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

50-00-0 formaldehyde

WEL	Short-term value: 2.5 mg/m ³ , 2 ppm Long-term value: 2.5 mg/m ³ , 2 ppm Carc
-----	---

67-56-1 methanol

WEL	Short-term value: 333 mg/m ³ , 250 ppm Long-term value: 266 mg/m ³ , 200 ppm Sk
-----	---

· **DNELs**

50-00-0 formaldehyde

Oral	Long-term - systemic effects, general population	4.1 mg/kg
Dermal	Long-term - systemic effects, worker	240 mg/kg
	Long-term - local effects, worker	0.037 mg/kg
	Long term - systemic effects, general population	102 mg/kg
	Long-term - local effects, general population	0.012 mg/kg
Inhalative	Acute - local effects, worker	1 mg/m ³
	Long-term - systemic effects, worker	9 mg/m ³
	Long-term - local effects, worker	0.5 mg/m ³
	Long-term - systemic effects, general population	3.2 mg/m ³
	Long-term - local effects, general population	0.1 mg/m ³

67-56-1 methanol

Oral	Acute - systemic effects, general population	5 mg/kg
	Long-term - systemic effects, general population	5 mg/kg
Dermal	Acute - systemic effects, worker	20 mg/kg
	Long-term - systemic effects, worker	20 mg/kg
	Acute - systemic effects, general population	5 mg/kg
	Long term - systemic effects, general population	5 mg/kg
Inhalative	Acute - local effects, worker	130 mg/m ³
	Acute - systemic effects, worker	130 mg/m ³

(Contd. on page 6)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 5)

	Long-term - systemic effects, worker	130 mg/m ³
	Long-term - local effects, worker	130 mg/m ³
	Acute - systemic effects, general population	26 mg/m ³
	Acute - local effects, general population	26 mg/m ³
	Long-term - systemic effects, general population	26 mg/m ³
	Long-term - local effects, general population	26 mg/m ³

· **PNECs**

50-00-0 formaldehyde

Aquatic compartment - freshwater	154 mg/L
Aquatic compartment - marine water	15.4 mg/L
Aquatic compartment - water, intermittent releases	1,540 mg/L
Aquatic compartment - sediment in freshwater	570.4 mg/kg
Terrestrial compartment - soil	23.5 mg/kg
Sewage treatment plant	100 mg/L

67-56-1 methanol

Aquatic compartment - freshwater	20.8 mg/L
Aquatic compartment - marine water	2.08 mg/L
Aquatic compartment - water, intermittent releases	1,540 mg/L
Aquatic compartment - sediment in freshwater	77 mg/kg
Terrestrial compartment - soil	100 mg/kg
Sewage treatment plant	100 mg/L

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device only when aerosol or mist is formed.

· **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 7)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 6)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mm

Value for the permeation: Level ≥ 480 min

· **As protection from splashes gloves made of the following materials are suitable:**

Recommended thickness of the material: ≥ 0.65 mm

Value for the permeation: Level ≥ 480 min

· **Eye/face protection**



Gauze goggles

· **Body protection:**

Use protective suit.

Full head, face and neck protection

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Liquid

· **Colour:**

Colourless

· **Odour:**

Acrid

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Undetermined.

· **Boiling point or initial boiling point and boiling range**

93-96 °C

· **Flammability**

Not applicable.

· **Lower and upper explosion limit**

· **Lower:**

5.5 Vol %

· **Upper:**

73 Vol %

· **Flash point:**

>62 °C

· **Auto-ignition temperature:**

~300 °C

· **Decomposition temperature:**

Not determined.

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity at 20 °C**

1.8-2.5 s (DIN 53211/4)

· **Dynamic at 20 °C:**

2 mPas

· **Solubility**

· **water:**

Fully miscible.

· **Partition coefficient n-octanol/water (log value)**

Not determined.

· **Vapour pressure at 20 °C:**

128 hPa

· **Density and/or relative density**

· **Density at 20 °C:**

1.08-1.1 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

(Contd. on page 8)

GB

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 7)

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** Not determined.
- **Explosive properties:** Product does not present an explosion hazard.
- **Solvent content:**
- **Organic solvents:** 49.0 %
- **Water:** 51.0 %
- **VOC (EC)** 49.00 %
- **Change in condition**
- **Evaporation rate** Not determined.
- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Heating
- **10.3 Possibility of hazardous reactions**
- Forms explosive gas mixture with air.
- Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** In the event of fire: See chapter 5
- **Additional information:** Explosible with air in a vaporous/gaseous state.

GB

(Contd. on page 9)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 8)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Toxic if swallowed, in contact with skin or if inhaled.
- **LD/LC50 values relevant for classification:**
Quantitative data on the toxicological effect of this product are not available.

Components	Type	Value	Species
ATE (Acute Toxicity Estimates)			
Oral	LD50	204 mg/kg (rat)	
Dermal	LD50	565 mg/kg (rabbit)	
Inhalative	LC50/4 h	6.12 mg/l	

50-00-0 formaldehyde

Oral	LD50	100 mg/kg (rat)	
Dermal	LD50	270 mg/kg (rabbit)	
Inhalative	LC50/4 h	3 mg/l (ATE)	

67-56-1 methanol

Oral	LD50	100 mg/kg (rat)	
Dermal	LD50	300 mg/kg (rabbit)	
Inhalative	LC50/4 h	3 mg/l (rat)	

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Danger of skin absorption.
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Risk of blindness.
Causes serious eye damage.
- **After inhalation:**
coughing
dyspnoea
Inhalation may lead to the formation of oedemas in the respiratory tract.
Strong caustic effect on skin and mucous membranes.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Suspected of causing genetic defects.
- **Carcinogenicity** May cause cancer.

Reproductive toxicity

67-56-1 methanol

NOAEL (Fertility)	0.13 mg/kg bw/day (rat)
-------------------	-------------------------

- **STOT-single exposure**
Causes damage to the central nervous system and the visual organs.
May cause respiratory irritation.
- **Other information (about experimental toxicology):**
After swallowing:
burns of mouth, pharynx, oesophagus and gastrointestinal tract.
Systemic effects:
narcosis
Further hazardous properties cannot be excluded.
- **Additional toxicological information:**
The product should be handled with the care usual when dealing with chemicals.

(Contd. on page 10)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 9)

· **Repeated dose toxicity**

50-00-0 formaldehyde

Inhalative	NOAEL	6 mg/l (rat)
------------	-------	--------------

67-56-1 methanol

Inhalative	NOAEL	1.06 mg/l (rat)
------------	-------	-----------------

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

Toxic for aquatic organisms

Toxic effect on fish and plankton.

Type of test	Effective concentration	Method	Assessment
--------------	-------------------------	--------	------------

50-00-0 formaldehyde

EC50/72 h	4.89 mg/l (Algae)
-----------	-------------------

EC50/48 h	5.8 mg/l (daphnia magna)
-----------	--------------------------

LC50/96 h	6.7 mg/l (fish)
-----------	-----------------

67-56-1 methanol

EC50/48 h	>10,000 mg/l (daphnia magna)
-----------	------------------------------

EC50/96 h	12,000 mg/l (Crustacea)
-----------	-------------------------

LC50/96 h	15,400 mg/l (fish)
-----------	--------------------

· **12.2 Persistence and degradability** The product is easily biodegradable.

· **12.3 Bioaccumulative potential**

Distribution log Pow<1.

Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:** disinfectant

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 3 (German Regulation) (Assessment by list): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Chemicals must be disposed of in compliance with the respective national regulations.

(Contd. on page 11)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 10)

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN2209

· **14.2 UN proper shipping name**

· **ADR, IMDG, IATA** FORMALDEHYDE SOLUTION

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 8 (C9) Corrosive substances.

· **Label** 8

· **IMDG, IATA**



· **Class** 8 Corrosive substances.

· **Label** 8

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Corrosive substances.

· **Hazard identification number (Kemler code):** 80

· **EMS Number:** F-A,S-B

· **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 5L

· **Excepted quantities (EQ)** Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category** 3

· **Tunnel restriction code** E

(Contd. on page 12)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 11)

- | | |
|--|--|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 2209 FORMALDEHYDE SOLUTION, 8, III |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

5%

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** Substance is not listed.
- **Seveso category H2** ACUTE TOXIC
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 50 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

H371 May cause damage to organs.

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 13)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 12)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 2: Germ cell mutagenicity – Category 2
Carc. 1B: Carcinogenicity – Category 1B
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

· *** Data compared to the previous version altered.**

Annex: Exposure scenario

- **Short title of the exposure scenario** Formulation and packing/repacking of substances and mixtures
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use**
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Avoid contact with the skin.
Avoid long-term or repeated skin contact.
Do not breathe gas/vapour/aerosol.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures** Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Tightly sealed goggles
Filter AX
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device only when aerosol or mist is formed.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 14)

Trade name: Formaldehyde 37-38% w/w stabilized with methanol

(Contd. of page 13)

- **Measures for consumer protection** Ensure adequate labelling.
- **Environmental protection measures**
- **Water**
Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.
- **Guidance for downstream users** No further relevant information available.

GB